


Technical sheet :

EP 16 EASY



| Technical characteristics | | | Metric |
|---------------------------|---|-----------|--------------------------|
| 1.1 | Manufacturer | | Manitou |
| 1.2 | Model Name | | EP 16 Easy |
| 1.3 | Power source | | Electrical |
| 1.4 | Operator type | | Pedestrian |
| 1.5 | Max. capacity | Q | 1600 kg |
| 1.6 | Load center of gravity | c | 600 mm |
| 1.8 | Load distance, centre of drive axle to fork | x | 980 mm |
| 1.9 | Wheelbase | y | 1415 mm |
| Weight | | | |
| 2.1 | Service weight | | 493 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 755 kg / 1338 kg |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 373 kg / 120 kg |
| Wheels | | | |
| 3.1 | Tires type | | Polyurethane |
| 3.2 | Dimensions of front wheels | | 250 x 80 |
| 3.3 | Dimensions of rear wheels | | 85 x 70 |
| 3.4 | Size of the stabilizer wheels | | 100 x 40 |
| 3.5.2 | Number of drive wheels / front wheels / rear wheels | | 1x + 2 / 2 |
| 3.6 | Front wheel gauge | b10 | 540 mm |
| 3.7 | Rear wheel gauge | b11 | 370 mm |
| Dimensions | | | |
| 4.15 | Fork height in low position | h13 | 85 mm |
| 4.19 | Overall length | l1 | 1770 mm |
| 4.20 | Length to face of forks | l2 | 620 mm |
| 4.21 | Overall width | b1 | 740 mm |
| 4.22 | Forks section / width / length | s / e / l | 64 mm x 170 mm x 1150 mm |
| 4.25 | Fork spread | b5 | 540 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 20 mm |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 1831 mm |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 2031 mm |
| 4.35 | Turning radius | Wa | 1556 mm |
| 4.4 | Mast lifting height | h3 | 125 mm |
| 4.9 | Height tiller min. | h14 | 1020 mm |
| 4.9 | Height tiller max. | h14 | 1350 mm |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 6 km/h / 6 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 30 mm/s / 45 mm/s |
| 5.3 | Lowering speed (laden / unladen) | | 50 mm/s / 35 mm/s |
| 5.7 | Gradeability (laden / unladen) | | 8 % / 15 % |
| 5.10 | Service brake | | Electro magnetic |
| Engine | | | |
| 6.1 | Drive motor rating S2 60 min | | 1.10 kW |
| 6.2 | Lift motor rating at S3 15% | | 0.80 kW |
| 6.3 | Battery according to DIN 43531/35/36 A, B, C | | DIN 43535-B |
| 6.4 | Battery voltage / capacity | | 24 V / 160 Ah |
| Miscellaneous | | | |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 75 dB |

EP 16 Easy - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes