

GCT 3-14

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ Multi-Function Joystick on Floating Armrest
- ✓ Automatic Parking Brake
- ✓ Polycarbonate Roof Window, FOPS Level 1
- ✓ Universal Skid Steer Attachment Quick Attach
- ✓ Enhanced Fork Tilt
- ✓ Battery Cut-Off

Key Specifications

- ✓ Maximum capacity 2,200 lbs.
- ✓ Standard Machine GVW 6,063 lbs.
- ✓ 3 Steering Modes - 2-Wheel, 4-Wheel, Crab
- ✓ Super Compact: W 4' 11" | H 6' 4" | L 11' 5"
- ✓ 35hp Yanmar Tier IV Fina Engine
- ✓ Maximum Lift of 14' 1"

SPECIFICATIONS

		IMPERIAL
Capacities	Max. capacity	2200 lb
	Max. lifting height	14 ft 1 in
	Max. outreach	8 ft 7 in
	Reach at max. height	3 ft 3 in
	Breakout force with bucket	1880 daN
Weight and dimensions	Shipping mass (min. / max.)	5622 lb / 6063 lb
	Ground clearance	11 in
	Wheelbase	7 ft
	Overall length to carriage (with hitch)	11 ft 5 in
	Overall length to carriage (without hitch)	11 ft 5 in
	Front overhang	2 ft 6 in
	Overall width	4 ft 11 in
	Overall cab width	2 ft 2 in
	Overall height	6 ft 4 in
	Tilt-down angle	116 °
	Tilt-up angle	23 °
		External turning radius (over tyres)
	Standard tires	CAMSO - MPT 552 - 10.0/75-15.3 124A8
Performances	Lifting	8.80 s
	Lowering	7 s
	Extension	6.40 s
	Retraction	4.30 s
	Crowd	3.40 s
	Dump	2.60 s
Engine	Engine brand	Yanmar
	Engine norm	Stage V / Tier 4 final
	Engine model	3TNV88C-DMU
	Number of cylinders - Capacity of cylinders	3 - 100 m ³
	I.C. Engine power rating / Power	35.10 Hp / 26.20 kW
	Max. torque / Engine rotation	77 ft/lbs @1950 rpm
	Drawbar pull (Laden)	2000 daN
	Reversible fan	Option
	Engine cooling system	3 radiators (water + hydraulic oil + fuel)
	HVO validated (according to EN 15940 standard)	Yes
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	16 mph
	Differential lock	Limited slip differential on front and rear axles
	Parking brake	Automatic negative parking brake
	Service brake	Hydraulic servo brake
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	13 US gpm - 3408 PSI
	Flow sharing distributor	Standard
Tank capacities	Hydraulic tank capacity	10 US gal
	Fuel tank	9 US gal
Noise and vibration	Noise at driving position (LpA) tested following NF EN 12053 norm	76 dB
	Noise to environment (LwA)	104 dB
	Vibration on hands/arms	< 2.50 m/s ²
Miscellaneous	Safety cab homologation	ROPS - FOPS cab (level 1)
	Controls	Joystick



STANDARD FEATURES

- Crab mode
- Battery cut-off
- USB Plug
- Adjustable and telescopic steering column
- Harmony screen
- Automatic parking brake
- 12Volt Power Port
- Document holder
- Connected machine
- 4 wheel drive
- Front and rear LED work lights on cab (x4 : 2 front + 2 rear)
- Cabin Rops and fops level I

OPTIONAL FEATURES

- Attachment hydraulic line
- Self-cleaning pre-filter
- Stop & Start
- Air suspension cloth-covered seat (GRAMMER)
- Auto Reversing Fan
- LED work lights on the boom (x2)
- Continuous flow hydraulics
- Attachment hydraulic locking
- Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT