Technical sheet:

MBL-X 920 94P ST3

Manitou is committed to bringing value to its backhoe loaders by incorporating advanced and robust features for multi-application capabilities. MBL X 920 is powered by Tier -II/III engine. The structure of MBL X 920 is durable and designed for intensive operations. It comes with the latest cabin design and unbreakable bonnet which promises to deliver higher up-time and require low maintenance, even after prolonged usage. Customers get quick returns on their investments on top of an optimum Total Cost of Ownership. It comes with an option of features such as AC, multipurpose bucket.





Capacities	Metric	
Capacities Wheelbase 2 wheels drive	2185 mm	
Wheelbase 4 wheels drive	2130 mm	
	2130 111111	
Weight and dimensions	7600 hrs	
Juladen weight	7620 kg	
Jnladen weight with 4 WD	7620 kg	
Jnladen weight with 4 WD 7 in 1	7908 kg	
Overall length	l1 7330 mm	
Overall width	b1 2330 mm	
Overall width with stabilizers extended - Center mount only	3910 mm	
Cabin height	h6 2830 mm	
Height of cab with air conditioning (option)	h6** 2860 mm	
Overall height	h17 3790 mm	
External turning radius over tyres (braked)	Wa1 3850 mm	
External turning radius over tyres (unbraked)	Wa1 4200 mm	
External turning radius over bucket (braked)	Wa5 5550 mm	
External turning radius over bucket (unbraked)	Wa5 5700 mm	
Standard tires front / rear	12.5 x 18 - 12 PR / 16.9 x 28-12	2PR
Optional tires (front / rear)	9 x 16 - 16 PR / 14 x 25 - 20 F	PR
Reach at travelling	c2 2098 mm	
Rear axle center to slew center	c3 1293 mm	
Departure angle	a2 20°	
Angle of Approach	a3 66°	
Ground clearance	m4 280 mm	
Performances		
Travel speed forward 1st / 2nd	5.40 km/h / 8.60 km/h	
Travel speed forward 3rd / 4th	19.90 km/h / 40 km/h	
Engine		
Engine brand	Perkins	
Engine model	1104D 44T Turbo Charged Water Cool	led Tier-II
Displacement	4.40 I	
Engine power (kW) / Gross Power	70 kW @ 2200 rpm	
Max. torque	395 Nm	
Battery voltage / capacity	12 V / 75 Ah	
Transmission	12 V / 73 All	
Transmission brand	Саптаго	
	4 / 4	
Number of gears (forward / reverse) Torque converter stall ratio	3.01:1	
Service brake		
	Wet disc brakes	
Hydraulics	4401/	
Hydraulic flow	142 l/min	
Main relief pressure	225 bar	
Tank capacities		
Hydraulic oil	90 I	
Cooling liquid	161	
Fuel	145	
Transmission oil	17.50 l	
Engine oil	9.10	
Oil rear axle	17.50	
Bucket		
Backhoe standard capacity	0.24 m³	
Width backhoe bucket	892 mm	
Loader standard capacity	1 m³	
Width loader bucket	2235 mm	
Miscellaneous		
Power steering	Yes	
Front steer axle of oscillation 2WD	20 °	
Front steer axle of oscillation 4WD	16 °	
Steering wheels (front / rear)	2/2	
Cab certification	Cabin ROPS - FOPS level 2	

Performance backhoe


	Standard dipper	Extending dipper	
		Retracted	
p1 - Max dig depth (mm)	4741	5815	
r1 - Max reach ground level to slew center (mm)	5730	7019	
r2 - Max loading reach (mm)	1996	4849	
Max operating height (mm)	5626	6637	
h22 - Max loading height SAE (mm)	-	4531	
Max loading height (mm)	3871	4849	
p2 - Max straight wall dig depth (mm)	2602	3991	
a10 - Max bucket rotation (°)	194	194	
Total side shift (mm)	1198	1198	
Dipper tearout (kgF)	4336	2644	
Bucket tearout (kgF)	5810	5219	
Hydraulic lift capacity (kg)	1460	812	


Performance loader


Max dump angle (°)	
h26 - Max operating height (loader version) (mm)	
h23 - Max dump height at 45° (mm)	
h24 - Max loadover height (mm)	
h25 - Max hinge pin height (mm)	
r3 - Max reach at full height 45° (mm)	
p3 - Below ground dig depth (mm)	
a13 - Rollback at ground (°)	
Shovel breakout (kgf)	
Arms breakout (kgF)	
Lifting capacity at full height (kg)	

Standard shovel
51
4230
2780
3310
3570
710
156
45
5229
5312
3819

MBL-X 920 94P ST3 - Dimensional drawing











Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes