Technical sheet:

# MBL-X 920 94P ST3

Manitou is committed to bringing value to its backhoe loaders by incorporating advanced and robust features for multi-application capabilities. MBL X 920 is powered by Tier -II/III engine. The structure of MBL X 920 is durable and designed for intensive operations. It comes with the latest cabin design and unbreakable bonnet which promises to deliver higher up-time and require low maintenance, even after prolonged usage. Customers get quick returns on their investments on top of an optimum Total Cost of Ownership. It comes with an option of features such as AC, multipurpose bucket.





Capacities	Metric
Wheelbase 2 wheels drive	2185 mm
Wheelbase 4 wheels drive	2130 mm
Weight and dimensions	
Unladen weight	7620 kg
Unladen weight with 4 WD	7620 kg
Unladen weight with 4 WD 7 in 1	7908 kg
Overall length	l1 7330 mm
Overall width	b1 2330 mm
Overall width with stabilizers extended - Center mount only	3910 mm
Cabin height	h6 2830 mm
Height of cab with air conditioning (option)	h6*** 2860 mm
Overall height	h17 3790 mm
External turning radius over tyres (braked)	Wa1 3850 mm
External turning radius over tyres (unbraked)	Wa1 4200 mm
External turning radius over tytes (urblaked)	Wa5 5550 mm
External turning radius over bucket (unbraked)	Wa5 5700 mm
Standard tires front / rear	12.5 x 18 - 12 PR / 16.9 x 28-12PR
Optional tires (front / rear)	9 x 16 - 16 PR / 14 x 25 - 20 PR
	c2 2098 mm
Reach at travelling Rear axle center to slew center	c2 2098 mm
	a2 20 °
Departure angle	
Angle of Approach	
Ground clearance	m4 280 mm
Performances Town I was all forward 1 at 4 (2) all	5.40 km /h / 0.60 km /h
Travel speed forward 1st / 2nd	5.40 km/h / 8.60 km/h
Travel speed forward 3rd / 4th	19.90 km/h / 40 km/h
Engine	
Engine brand	Perkins
Engine model	1104D 44T Turbo Charged Water Cooled Tie
Displacement	4.40
Engine power (kW) / Gross Power	70 kW @ 2200 rpm
Max. torque	395 Nm
Battery voltage / capacity	12 V / 75 Ah
Transmission	
Transmission brand	Сапаго
Number of gears (forward / reverse)	4 / 4
Torque converter stall ratio	3.01:1
Service brake	Wet disc brakes
Hydraulics	
Hydraulic flow	142 l/min
Main relief pressure	225 bar
Tank capacities	
Hydraulic oil	90 I
Cooling liquid	161
Fuel	145
Transmission oil	17.50 I
Engine oil	9.10
Oil rear axle	17.50 I
Bucket	
Backhoe standard capacity	0.24 m³
Width backhoe bucket	892 mm
Loader standard capacity	1 m³
Width loader bucket	2235 mm
Miscellaneous	
Power steering	Yes
Front steer axle of oscillation 2WD	20 °
Front steer axle of oscillation 4WD	16 °
Steering wheels (front / rear)	2/2

### Performance backhoe


	Standard dipper	Extending dipper
		Retracted
p1 - Max dig depth (mm)	4741	5815
r1 - Max reach ground level to slew center (mm)	5730	7019
r2 - Max loading reach (mm)	1996	4849
Max operating height (mm)	5626	6637
h22 - Max loading height SAE (mm)	-	4531
Max loading height (mm)	3871	4849
p2 - Max straight wall dig depth (mm)	2602	3991
a10 - Max bucket rotation (°)	194	194
Total side shift (mm)	1198	1198
Dipper tearout (kgF)	4336	2644
Bucket tearout (kgF)	5810	5219
Hydraulic lift capacity (kg)	1460	812


## Performance loader


Max dump angle (°)
h26 - Max operating height (loader version) (mm)
h23 - Max dump height at 45° (mm)
h24 - Max loadover height (mm)
h25 - Max hinge pin height (mm)
r3 - Max reach at full height 45° (mm)
p3 - Below ground dig depth (mm)
a13 - Rollback at ground (°)
Shovel breakout (kgf)
Arms breakout (kgF)
Lifting capacity at full height (kg)

Standard shovel
51
4230
2780
3310
3570
710
156
45
5229
5312
3819

#### MBL-X 920 94P ST3 - Dimensional drawing











#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes