Technical sheet:

# **MLT 730-115 V CP**







	MLT 730-115 V CP Created on December 22, 2024 at 1:24 A
Capacities	Metric
Max. capacity	Q 3000 kg
Max. lifting height	h3 6.75 m
Max. outreach	4.35 m
Reach at max. height	1.30 m
Breakout force with bucket	4633 daN
Weight and dimensions	
Unladen weight (with forks)	6820 kg
Ground clearance	m4 0.28 m
Wheelbase	y 2.69 m
Overall length to carriage (with hitch)	l11 5.08 m
Overall length to carriage (without hitch)	l3 4.93 m
Front overhang	1.55 m
Overall width	b1 2.06 m
Overall cab width	b4 0.95 m
Overall height	h17 2.14 m
Tilt-down angle	a5 133 °
Tilt-up angle	a4 13 °
External turning radius (over tyres)	Wa1 3.65 m
Standard tires	Alliance - A580 - 400/70 R20 149A8
Drive wheels (front / rear)	2/2
Steering wheels (front / rear)	2/2
Performances	
Lifting	5.80 s
Lowering	5.70 s
Extension	6.60 s
Retraction	3.80 s
Crowd	3 s
Dump	2.50 s
Engine	
Engine brand	Deutz
Engine norm	Stage V
Engine model	TCD 3.6 L4
Number of cylinders - Capacity of cylinders	4 - 3621 cm <sup>3</sup>
I.C. Engine power rating / Power	116 Hp / 85 kW
Max. torque / Engine rotation	460 Nm @1600 rpm
Drawbar pull (Laden)	5850 daN
Reversible fan	Standard
Engine cooling system	4 radiators (water + intercooler + oil + fu
HVO validated (according to EN 15940 standard)	Yes
Transmission	163
Transmission type	M-Varioshift
Number of gears (forward / reverse)	2/2
Max. travel speed (may vary according to applicable regulations)	38 km/h
Differential lock	Limited slip differential on front axle
	Manual
Parking brake Service brake	Manual Oil-Immersed multi-discs braking on front
	Un-inititiersed mutu-discs draking on front
Hydraulics	
Hydraulic pump type	Gear pump 106 I/min - 250 bar
Hydraulic flow - Pressure	
Flow sharing distributor	Option
Tank capacities	A
Hydraulic tank capacity	941
Fuel tank	781
Diesel Exhaust fluid (AdBlue® type)	13
Noise and vibration	
Noise at driving position (LpA) tested following NF EN 12053 norm	73 dB
Noise to environment (LwA)	106 dB
Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	
Tractor homologation	Tractor homologation
Safety cab homologation	Cabin ROPS - FOPS level 2
Controls	JSM

## Optional tires tab

	Overall height	Overall width
ALLIANCE - A331 - 500/45-20 159A8	2.10 m	2.20 m
MICHELIN - BIBLOAD - 400/70 R20 149A8	2.18 m	2.06 m
MICHELIN - XMCL - 400/70 R20 149A8	2.14 m	2.06 m


### MLT 730-115 V CP - Dimensional drawing





### MLT 730-115 V CP - Load chart

#### Machine on tires with forks Metric







#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes