Technical sheet:


MLT-X 841 - 145 PS+






	MLT-X 841 - 145 PS+ Created on December 14, 2025 at 4:19 PM U
Capacities	Metric
Max. capacity	Q 4100 kg
Max. lifting height	h3 7.60 m
Maximum outreach	4.45 m
Reach at max. height	0.90 m
Breakout force with bucket	5268 daN
Weight and dimensions	
Unladen weight (with forks)	9160 kg
Ground clearance	m4 0.43 m
Wheelbase	y 2.88 m
Overall length to carriage (with hitch)	l11 5.40 m
Overall length to carriage (without hitch)	13 5.23 m
Front overhang	1.50 m
Overall width	b1 2.39 m
Overall cab width	b4 0.99 m
Overall height	h17 2.42 m
Tilt-down angle	a5 135°
Tilt-up angle	a4 12°
External turning radius (over tyres)	Wa1 3.74 m
Standard tires	Michelin - XMCL - 460/70 R24 159A8
Drive wheels (front / rear)	2/2
Steering mode	Manicrab, 2 wheel steer, 4 wheel steer, Crab mode
Performances	
Lifting	6.40 s
Lowering	4.60 s
Extension	6.10 s
Retraction	5.20 s
Crowd	3 s
Dump	2.20 s
Engine	
Engine brand	Yanmar
Engine norm	Stage IIIA
Max. fuel sulphur content	1000 ppm
Engine model	4TN107HT-5SMUF
Number of cylinders - Capacity of cylinders	4 - 4567 cm ³
Engine power (Hp / kW)	141 Hp / 105 kW
Max. torque / Engine rotation	602 Nm @1500 pm
Drawbar pull (Laden)	8727 daN
Reversible fan	Standard
nevelsible (all	4 radiators (water + intercooler + hydraulic oil +
Engine cooling system	transmission oil)
Transmission	
Transmission type	Torque converter with powershift gearbox
Gearbox	M-Shift
Number of gears (forward / reverse)	5/3
Max. travel speed (may vary according to applicable regulations)	40 km/h
Differential lock	Limited slip differential on front and rear axles
Parking brake	Automatic negative parking brake
	Oil-immersed multi-discs braking on front & rear
Service brake	axles
Hydraulics	
Hydraulic pump type	Variable displacement pump
Hydraulic flow - Pressure	200 l/min - 270 bar
Flow sharing distributor	Standard
Tank capacities	
Hydraulic tank capacity	141 I
Fuel	142
Noise and vibration	
Noise at driving position (LpA) tested following NF EN 12053 norm	69 dB
Noise to environment (LwA)	105 dB
Vibration on hands/arms	2.50 m/s²
Miscellaneous	
Tractor homologation	Tractor homologation
Cab certification	Cabin ROPS - FOPS level 2
Controls	JSM

Optional tires tab




MLT-X 841 - 145 PS+ - Dimensional drawing



MLT-X 841 - 145 PS+ - Load chart

Machine on tires with forks Metric







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes