

R135 GEN:2

COMPACT LOADERS



Key Features

- ✓ Loft Effort Control Choices
- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Self-Leveling Hydraulic Lift Action
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar or Hand/Foot Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat

Key Specifications

- ✓ Operating Capacity (50%) - 612 kg (1,350 lbs.)
- ✓ Overall height to top of ROPS - 1930 mm (76")
- ✓ Gross Power - 34.3 kW (46.6 hp) @ 2800 rpm
- ✓ Yanmar / 4TNV88C / Stage 4
- ✓ 146.2 Nm (108 ft.-lbs.) @ 1820 rpm max torque
- ✓ 2784 mm (110") height to hinge pin
- ✓ 1364 mm (53.7") machine width - less bucket
- ✓ 2327 kg (5,130 lbs.) operating weight

SPECIFICATIONS

IMPERIAL		
Capacities	Operating Capacity At 50% Tipping Load	1350 lb
	Rated Operating Capacity with Optional Counterweight	1499 lb
	Operating Weight	5255 lb
	Tipping capacity	2700 lb
Weight and dimensions	Wheelbase	37 in
	Overall Operating Height - Fully Raised	144 in
	Height to Hinge Pin - Fully Raised	110 in
	Dump angle at full height	40 °
	Dump height	83 in
	Overall length with bucket	121 in
	Dump reach - Full height	23 in
	Rollback at ground	28 °
	Seat to ground height	34 in
	Overall width less bucket	54 in
	Bucket Width	54 in
	Ground clearance	8 in
	Overall length - Less Bucket	93 in
	Clearance Radius - Front with Bucket	73 in
Performances	Travel speed (unladen)	8 mph
	Standard tires	10.00 x 16.5 HD
Engine	Engine brand	Yanmar
	Engine model	4TNV88C
	Engine norm	Stage IV, Tier 4 final
	Gross Power	46 Hp
	Max. torque / Engine rotation	108 ft/lbs / 1820 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	2.30 kW
Hydraulics	Standard flow - Auxiliary hydraulics	17 US gpm
Tank capacities	Fuel tank	16 US gal
	Hydraulic tank capacity	9 US gal
	Displacement	0.58 US gal
Noise and vibration	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	0.81 m/s²
	Vibration on hands/arms	< 1.77 m/s²



Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT